

STEICO *sprucefloor*

Plywood flooring panels

Flooring Systems
naturally made from timber



STEICO *sprucefloor* is a superior flooring solution designed for joisted and floating floor applications. A high quality WISA spruce plywood floor panel with a T&G profile which matches other STEICO boards.

STEICO *sprucedek* features a peel off waterproof film to protect boards against both the weather and site spoil.



- Surface grade II/III to BS EN 635-3:1995 sanded both sides
- PEFC Certification and CE marked
- Available in 18 or 22 mm
- Standard size 2400x 600 mm
- TG Profile matches STEICO chipboard for full flexibility
- Tongued and grooved on four edges
- BS 5268 part 2:2002
- Phenolic resin bonded to EN 314-2 class 3 exterior (WBP)
- Available with a peel-off waterproof protective surface.
- Full range of fixing accessories supplied

For more information please visit our website at www.steico.co.uk



| STEICO sprucefloor BOARD SPECIFICATIONS

Thickness [mm]	Board Coverage [mm]	Weight [kg / m ²]	Pieces per pallet	Pallet Coverage [m ²]	Pallet weight [kg]
18	2400 x 600	8.64	100	144.00	ca. 1250
22	2400 x 600	10.56	82	129.60	ca. 1250

| STEICO sprucefloor PRODUCT DESCRIPTION

STEICO sprucefloor is a T&G profiled plywood flooring panel available in 18 mm (7 ply) and 22 mm (9 ply) thicknesses. The edge profile is identical to other panels available in the STEICO range and may be used in combination with these panels. It is especially suitable for kitchens and bathrooms where extra moisture protection is required.

STEICO sprucefloor is constructed from thick (2.6 – 3.2 mm) spruce veneers with long grain face veneers. For normal domestic loadings to BS6399: part 1: 1996, the 18 mm board may be used with joists spaced at a maximum of 600 mm centres.

The product is intended for use in hazard classes 1 (dry conditions) & 2 (risk of wetting/humid conditions) as defined in BS EN 335-3:1996.

STEICO sprucefloor has a thermal conductivity of 0.14 W degrees C and a Class 3 surface spread of flame rating when tested to BS 476:Part 7.

| STEICO sprucedek PRODUCT DESCRIPTION

The high quality sprucefloor panel can be supplied with a "weatherdek" green peel-off film to protect boards from temporary exposure to the weather (<42 days exposure when fixed correctly). The protective surface also protects against site spoil and moisture ingress making it also ideal in floating floor applications.

STEICO sprucedek is supplied as part of a floor system including edge sealing tape and PVAD3 jointing adhesive. The boards can also be laid using our Fast-Fix system which eliminates many mechanical fixings. This is the ideal method when used

with STEICO engineered floor joists to achieve a squeak free floor.

Fixing

For full fixing instructions please refer to our four page fixing instruction brochure which explains in detail the options available.



Your STEICO Dealer

www.steico.co.uk