

STEICO *multi box*

Sealing system for all common installations



- This item is not a standard UK item. Please contact STEICO UK to clarify availability
- Ideal for airtight connections of electrical installations in wall and ceiling areas
- Simple processing
- Provides space for up to 3 Dry Lining Back Boxes (depth up to 62 mm)
- Can be extended as required

Application area



- Sealing system for all common installations in walls and ceiling area
- Electrical installations in timber frame walls without installation level

Technical data

| | |
|----------------------------------|----------------------|
| Reaction to fire | Fire class HB (UL94) |
| Density [g/cm ³] | 1.03 |
| Tensile modulus (1 mm/min) [MPa] | 1650 |

Forms of delivery

Delivery in handy boxes

| Width [mm] | Content | Number/pack. [pcs.] | Length [mm] | Depth [mm] |
|------------|--|---------------------|-------------|------------|
| 125 | 1 installation box + 1 sealing plug each DN 20 and DN 32 + 1 empty pipe 1.30 m DN 20 and 1.30 m DN 32 each + 1 GD 22 lead-through sleeve Ø 25 - 32 mm + 1 GD 21 lead-through sleeve Ø 15 - 22 mm | 1 | 260 | 65 |

Weight and packing

Delivery in handy boxes

| Thickness [mm] | Length [mm] | Width [mm] | Packaging/pack. Paper/cardboard (approx.) [kg] |
|----------------|-------------|------------|--|
| 65 | 260 | 125 | 0.30 |

Notes

Storage

- Protect from damage
- Protect from UV radiation
- Store in a cool and dry place

Installation

- Regional and national regulations and Building laws have to be fulfilled
- Under www.steico.com/technik-verarbeitung or the enclosed QR code, you will find the processing instructions for this product under the category „Verarbeitungsanleitung STEICOMulti Dichtungssystem inkl. Klebe- und Dichtstoffe“.
- (STEICO*multi box* Verarbeitungsanleitung)

☰ Caption

other abbreviations

- pal.** Pallet
- T&G** Tongue and Groove
- pac.** Packaging
- approx.** Approximately