

STEICO *multi cover 5*

Wear resistant, rain proof vapour barrier



- Excellent walkability even in wet conditions
- 2 integrated self-adhesive zones
- Extremely high tear resistance
- Can be used as temporary covering (DN >10°)
- 3-ply, coated PP fleece, grid-reinforced

Application area



- Vapour retarder for exterior roof and wall constructions
- Robust vapour retarder for the renovation of existing upper storey ceilings

Technical data

Production and designation	EN 13984: 2013
Fire class (RTF) according to EN 13501-1	E
Temperature resistance [°C]	-40 to +80
Max. tensile force longitudinal	320
Max. tensile force transverse	270
Elongation at Max. tensile force longitudinal [%]	40
Elongation at Max. tensile force transverse [%]	40
Tear resistance longitudinal [N]	350
Tear resistance transverse [N]	300
Resistance to water penetration	W1
Seepage resistance after artificial ageing	W1
Durability of the water vapour permeability resistance to artificial ageing	passed
Suitable as a temporary roof cover	4 Weeks
Outdoor exposure	3 Months
s_d -value [m]	5,00

Additional technical data

thickness [mm]	s_d value [m]
0.45	5.00

STEICO *multi cover 5*

Wear resistant, rain proof vapour barrier

Forms of delivery

Rolled product

Length [mm]	Width [mm]	Number/pal. [pcs.]	Area/roll [m ²]
50000	1500	20	75

Weight and packing

Rolled product

Length [mm]	Width [mm]	Weight/m ² [kg]	Weight/pcs. [kg]	pac./pal. paper/ cardboard (ap- prox) [kg]	pac./pal. plastic (approx) [kg]	pac./pal. wood (approx) [kg]	Weight./pal. (approx.) [kg]
50000	1500	0.15	11.3	38.00	2.5	16.2	290

Notes

Storage

- Store in a dry place, protected from dirt, sun and moisture

Disposal

- dispose with normal construction waste, observe applicable legal guidelines

Cutting

- The airtight membrane can be cut to size using a sharp knife or a cutting tool suitable for membranes

Processing

- Clean the roof surface in advance and remove any obstructions (nails and sharp objects)
- Lay the membrane with the printed side facing the installer
- Lay parallel to the eaves with at least 10 cm overlap
- Only fix within the overlap area (e.g. staples)
- Only activate the longitudinal self-adhesive zones after fixing the membrane by removing the protective strip
- Component connections and penetrations must be made airtight with STEICO system accessories
- Can be used as a vapour barrier regardless of the roof pitch
- Can be used as a temporary covering from a roof pitch of > 10°
- Regional and national regulations and Building laws have to be fulfilled

Certificates and quality management



STEICO *multicover 5*

Wear resistant, rain proof vapour barrier

☰ Caption

other abbreviations

pal. Pallet

T&G Tongue and Groove

pac. Packaging

approx. Approximately