

STEICO *multi fill*
 Permanently flexible ETICS joint adhesive



- Permanently elastic with high compressive strength
- Can be used indoors and outdoors
- Can be plastered over
- UV stable
- Rapid complete curing
- Can be used wet on wet
- High adhesion on various substrates
- Free from isocyanate, solvent and silicone

Application area



- Joint filler for joint widths up to max. 6 mm
- Repair adhesive (bonding of Wood fiberboard fitting pieces)
- Bonding STEICO*fix / fix 2.0* outside in ETICS construction

Technical data

Range [m]	35-25/25-10/10-6
Joint width [mm]	2-3 / 3-5 / 5-6
Temperature resistance [°C]	-40/+100
Processing temperature min. [°C]	+5
Colour	Brown
Consistency	Medium-viscosity, paste-like
Density [g/cm ³]	1.50
Curing 24 h (20°C, 50% RH) [mm]	4
Breaking strain (ISO 37) [%]	370
Breaking strength (ISO 37) [MPa]	2,5
Discolouration	none

Forms of delivery

Supplied in handy boxes

Form of delivery	Size [ml]	Number/pack. [pcs.]
Cartridges	310	12

Weight and packing

Supplied in handy boxes

Size [ml]	Weight/pcs. [kg]	Weight/pack. [kg]	Packaging/pack. Paper/cardboard (approx.) [kg]
310	0.5	6.50	0.20

Notes

Storage

- Store in a cool and dry place at +15 to +25 °C
- Protect from heat, cold and UV radiation
- Can be stored for at least 12 months

Disposal

- Dispose of hardened material residues according to EWC 17 09 04 (mixed construction and demolition waste)

Cutting

- Can be applied with conventional cartridge or tubular bag guns

Occupational health and safety

- Additional information in the safety data sheet must be observed.

Installation

- Apply STEICO*multi fill* to one side of the dry, grease-free and dust-free bonding surface
- Good adhesion to paint systems, metals, glass, ceramics, non-porous substrates in general and various plastics
- Although good results are also achieved in practice without an adhesive primer, it is recommended to use STEICO*multi primer* on concrete.
- However, in the case of inhomogeneous, different substrates, the adhesion values that can be achieved should first be determined by means of a test
- The skin formation time is significantly shorter in high humidity or after spraying the adhesive with water
- Suitable for bonding butt joints in ETICS
- Regional and national regulations and Building laws have to be fulfilled

Certificates and quality management



☰ Caption

other abbreviations

- pal.** Pallet
T&G Tongue and Groove
pac. Packaging
approx. Approximately