

**STEICO** *multi nail*  
Nail tight tape



- Additional sealing measure for counter battens fitted over STEICO*multi UDB* or STEICO*safe*
- Single-sided self-adhesive, excellent adhesive properties
- Easy handling
- High elasticity
- Resistant to ageing

**Application area**



- Additional sealing measure for screw or nail connections of the counter battens when using STEICO*multi UDB* or STEICO*safe* as underlayment

**Technical data**

Temperature resistance [°C]	-40 to +80
Processing temperature [°C]	≥ +5
Volume weight [kg/m <sup>3</sup> ]	approx. 30
Lengthwise tensile strength [N/mm <sup>2</sup> ]	0,34
Transverse tensile strength [N/mm <sup>2</sup> ]	0,22
Lengthwise stretch at break	135
Transverse stretch at break	115
Material	Closed cell polyethylene

**Forms of delivery**

Supplied in handy boxes

Length [mm]	Width [mm]	Number/pack. [pcs.]
30000	50	10
30000	80	6

### Weight and packing

Supplied in handy boxes

Thickness [mm]	Length [mm]	Width [mm]	Weight/m <sup>2</sup> [kg]	Weight/pcs. [kg]	Weight/pack. [kg]	Packaging/pack. Paper/cardboard (approx.) [kg]
3	30000	50	0.01	0.2	2.60	0.60
3	30000	80	0.01	0.3	2.60	0.60

### Notes

#### Storage

- Store in a dry place, protected from dirt, sun and moisture

#### Ingredients

- Cell-closed polyethelene with synthetic rubber

#### Disposal

- dispose with normal construction waste, observe applicable legal guidelines

#### Cutting

- Sharp knife or other suitable cutting tool

### Installation

- The substrate must be clean, dust-free and dry
- The one-sided self-adhesive tape is applied directly from the roll and fixed to the STEICO*multi UDB* underlayment in the area of the counter-battens.
- The counter-batten is then positioned directly over the applied tape and mechanically fastened (nails and screws).
- The relevant technical regulations and standards must be observed
- Regional and national regulations and Building laws have to be fulfilled

### ☰ Caption

#### other abbreviations

**pal.** Pallet

**T&G** Tongue and Groove

**pac.** Packaging

**approx.** Approximately