

STEICO *multi tape P*

High performance tape with kraft paper



- Solvent-free
- Temperature resistant between -40 and + 100 °C
- Can be torn by hand
- Sturdy cardboard carrier
- Patches ideal for sealing injection holes

Application area



- Joint and connection bonding in the STEICO membrane system, as on wood-based panels e.g. OSB

Technical data

Temperature resistance [°C]	-40 to +100
Processing temperature [°C]	+5
Adhesive	Acrylic dispersion, solvent-free
Adhesive backing	Kraft paper with PE protective coating
Colour	White
Thickness (without release paper) [mm]	approx. 0,3
Peeling strength	fulfilled according to DIN 4108/11
Peel strength after ageing	fulfilled according to DIN 4108/11

Forms of delivery

Length [mm]	Width [mm]	Plaster [mm]	Number/roll [plaster]	Number/pack. [pcs.]
40000	60	-	-	10

Roll with individual patches

Length [mm]	Width [mm]	Plaster [mm]	Number/roll [plaster]	Number/pack. [pcs.]
40000	200	180*180	222	1

STEICO *multi tape P*

High performance tape with kraft paper

Weight and packing

Length [mm]	Width [mm]	Weight/m ² [kg]	Weight/pcs. [kg]	Weight/pack. [kg]	pac./pal. paper/cardboard (approx) [kg]
40000	60	1.09	1.1	11.50	0.50

Roll with individual patches

Length [mm]	Width [mm]	Weight/m ² [kg]	Weight/pcs. [kg]	Weight/pack. [kg]	pac./pal. paper/cardboard (approx) [kg]
40000	200	3.73	3.7	4.20	0.50

Notes

Storage

- Store in a cool and dry place at +5 to +25 °C
- Protect from heat, cold and UV radiation

Ingredients

- Acrylic dispersion (solvent-free), kraft paper with PE protective coating

Disposal

- dispose with normal construction waste, observe applicable legal guidelines

Cutting

- Sharp knife or other suitable cutting tool

Installation

- STEICO *multi tape P* can only be used indoors
- Substrates must be stable, dry, and free of dust and grease.
- Align STEICO *multi tape P* in the centre, remove the release paper step by step and rub the adhesive tape vigorously in the process
- Apply STEICO *multi tape P* without tension or creases. If tensile forces occur, the substrate must also be mechanically fastened.
- To improve adhesion, especially on wood-based panels, additional pressing with a pressure roller is recommended
- Bonding must not be in standing water. Bonding in saunas and swimming pools is also not permitted.
- Regional and national regulations and Building laws have to be fulfilled

Certificates and quality management



STEICO *multi tape P*

High performance tape with kraft paper

☰ Caption

other abbreviations

pal. Pallet

T&G Tongue and Groove

pac. Packaging

approx. Approximately